



Print Date:	04/11/2025	Specification Log Number		6779300		
Specification & Product Information Sheet						
Product Name	Toppits Professional Wrapmaster 4500 PVC Cling Film Refill Rolls			Product Code	31C46 SAP Code 6779300	
Material	VLMF Cling Film, in compliance with EU Regulation No. 10/2011 and amendments, and other food contact legislation. For use with all food stuffs except pure fat and oils and food stored in an oily medium.					
Roll Dimensions	Length	300mtrs (+/- 2.5%)	Width	445 - 455mm	Micron	5.9 - 7.2 micron
Labels Inner	N/A			Labels Outer	Batch-code details to be stamped on the inside of the box or printed on the end of the cardboard core & One Label containing Product code/Description/Barcode on outer.	
Country Of Origin & Manufacture	Country Of Origin France Manufactured in Poland.			Barcode Single	N/A	
Core Size	58T21 - 462mm x 30mm x 3mm + 60M98A Black Plastic Bung			Barcode Pack	N/A	
Packaging Inner Box	N/A			Barcode Case	5023139314638	
Packaging Outer Box	Toppits Wrapmaster 4500 Outer Cardboard box.			Specification Instructions	61M11 security label must be used to ensure that the box stays closed. Rolls must have straight & sufficient Roll back for easy-start function.	
Packing Instructions				Pallet Configuration		
Pack 3 rolls per outer case				Euro Pallet - 7 Cases per layer, 10 Layers high, 70 Cases per pallet.		
Weights & Dimensions (Approximate)		Packaging Waste Weights (Approximate) (G)				
		Primary Packaging	Secondary	Secondary	Transit	
Inner Weight (G) (Gross)	N/A	Recycled Cardboard/Paper	255	0	0	2960
Pack Weight (G) (Gross)	N/A	Recycled Cardboard/paper Core	290.5	0	0	0
Case Weight (KG) (Gross)	3.8	Plastic LDPE	0	0	0	415
Inner Dimensions (CM) W x H x D	N/A	Plastic PP	21.9	0	0	0
Pack Dimensions (CM) W x H x D	N/A	Plastic Blade	0	0	0	0
Case Dimensions (CM) W x H x D	50 x 8.5 x 23.5	Metal Blade	0	0	0	0
Intrastat/Commodity Code						
39204310						
Product Claims - Foil/Film/Baking Paper/Greaseproof Paper						
Recyclable			Compostable			
No			No			
Pallet Wrapping						
Cardboard corner to be placed on each corner of the pallet & Stretch wrapped secured to pallet, minimum of 8 revolutions						